

Chassis Platform	LP 407 / 34 BS IV CNG; 24 seater
Engine	TATA 3.8 SGI BS-IV ENGINE; Water cooled naturally-aspirated, direct injection CNG engine
Maximum Power	62 kW (85 kW) @ 2500 r/min
Torque	270 Nm @1200-1500 r/min
Gear Box	GBS-27 synchromesh; 5 fwd + 1 rev
Clutch	280 mm Single plate dry friction type
Suspension	Semi elliptical leaf spring at front and rear; Hydraulic double acting telescopic type at front and rear; Anti-roll bar (front & rear)
Tire Size	7.5 X 16 - 16 PR Cross Ply
Steering	Hydraulic power assisted Steering
Brakes	Vaccum assisted dual circuit hydraulic with tandem master cylinder
No of CNG Cylinders	310 l / 245 l / 180 l
Wheelbase	3400 mm
Front Overhang	1430 mm
Rear Overhang	2040 mm
No. of Seats	24
Maximum Width	2200 mm
Passenger Door	1 jack knife type
Overall Length	6970 mm
Overall Height In Laden Condition	2800 mm
Turning Circle Diameter	12300 mm
Maximum Speed	94 km/h
GVWR	6520 kg
Battery	12 V
Alternator Capacity	65 A
Battery Capacity	120 Ah