

Model Name	Low entry Tarmac on LPO 1623
Chassis Platform	LPO 1623 BS IV CNG
Engine	ISB 5.9G BSIV ENGINE (CUMMINS)
Maximum Power	172 kW at 2800 r/m
Maximum Torque	678 Nm at 1700 r/m
Gear Box	Allison's Automatic Transmission; T270R 6 forward, 1 reverse
Suspension	Pneumatic suspension at front & rear Hydraulic double acting telescopic type shock absorber at front and rear
Retarder	In -Built Hydrodynamic Retarder
Tyre Size	11R22.5 Radial Tyres
Steering	Hydraulic Power Steering
Brakes	Dual circuit,full air S-CAM brake at rear, disc brake at front
No of CNG Cylinders	720 l
Wheelbase	6300 Mm
Front Overhang	2255 Mm
Rear Overhang	3055 Mm
No. of Seats	Customized
Maximum Width	2600 Mm
Passenger Door	In swing Front door , outswing rear door
Overall Length	12000 Mm
Overall Height In Laden Condition	3350 Mm
Turning Circle Diameter	19700 Mm
Maximum Speed	76 km/H
GVW	16200 Kg
Electricals	2 x 12 V, 180 Ah; Alternator Capcity 90 A